



# TN7301

## Fire Telephone Jack

### Features and Benefits

- Non-polarized two-wire for communication and talk, cost effective for wiring.
- Connect to Addressable TN7300 Jack Socket

### Overview

TN7300 Addressable Fire Telephone Jack Socket (called the Jack Socket for short), a telephone port installed in the field can detect the plug in and hang up of an extension handset. It is suitable for hotels, restaurants, office buildings, teach buildings, banks, warehouses, libraries, computer rooms and switching rooms.

The Jack Socket can constitute a fire telephone system together with TN7000 Fire Telephone Control Panel, TN7100 Addressable Handset, TN7101 Extension Handset and TN7301 Fire Telephone Jack Socket.

### Technical Specification

Power Rating	
Power Rated	24VDC ( 20VDC – 28 VDC)
Current Consumption	20 $\mu$ A
Jack Socket	
Connection	Connect to Addressable TN7300 Jack Socket
End of line	24k $\Omega$ (20k $\Omega$ ~25k $\Omega$ )
Material / Colour	ABS / Red-White
Dimension	L:86.6 mm x W:30 mm x H:86.6 mm
Weight	0.065 Kg
Operating Temperature	-10°C to +55°C
Humidity	0 to 95% Relative Humidity, Noncondensing