



# TX7724

## Fire Emergency Telephone

### Features and Benefits

- 24 Zone addressable fire telephone center on Standard 19inch 3U rack mounting
- 2-way voice communication and call panel to panel with Automatic voice recording.
- Each zone supports up to 5 fire phone station and Networkable up to 8 Fire Telephone panels
- Call divert feature to the main panel if slave panel do not attend the call
- Operator can ring outstations and fixed handsets and can select group call.
- Communication line and network cable monitoring
- Built-in Sounder and Mute button

### Technical Specification

Power Rating	
Operating Voltage	24 VDC (External EN54-4 PSU is required)
Standby Current	200mA
Alarm Current	1000mA Maximum
Capacity	
Panel	Up to 24 zone
Panel to Panel	Up to 8 units
Panel to Fire Phone Station	Up to 5 Fixed and Hands-free or up to 7 jack points
Communication Signal	
Frequency	300 to 3400 Hertz
Crosstalk	-60dB
Transmission Loss	5dB
End of Line Resistor	10kΩ±0.5KΩ

Material / Colour	Flat sheet Metal / Dark Gray
Dimension	482.5mm x 132.5mm x 225mm
IP Grade	IP30 Indoor Use
Gross Weight	4.2Kg
Operating Environment	
Temperature	-5°C~+40°C
Relative Humidity	≤95%, non-condensing